

Straight Blade Plugs & Receptacles

	15 Ampere		20 Ampere		30 Ampere		50 Ampere		60 Ampere	
	Receptacle	Plug	Receptacle	Plug	Receptacle	Plug	Receptacle	Plug	Receptacle	Plug
2 Pole, 2 Wire Non-Grounding										
125V	1 1-15R									
250V	2			2-20P						
2 Pole, 3 Wire Grounding										
125V	5 5-15R	5-15P	5-20R	5-20P	5-30R	5-30P		5-50P		
250V	6 6-15R	6-15P	6-20R	6-20P	6-30R	6-30P	6-50R	6-50P		
277VAC	7 7-15R	7-15P	7-20R	7-20P		7-30P		7-50P		
3 Pole, 3 Wire Non-Grounding										
125/250V	10		10-20R	10-20P	10-30R	10-30P	10-50R	10-50P		
3 Pole, 4 Wire Grounding										
125/250V	14		14-20R	14-20P	14-30R	14-30P	14-50R	14-50P		14-60P
3ø250V	15			15-20P	15-30R	15-30P	15-50R	15-50P	15-60R	15-60P
4 Pole, 4 Wire Non-Grounding										
3øY 120/208V	18		18-20R	18-20P					18-60R	18-60P

Open Slots

Indicate receptacle configurations (female).



Closed Slots

Indicate plug blade configurations (male).



Labels and Their Meanings

X, Y, Z	Hot Lead
W	Neutral Lead
G	Grounding Lead

